AN INTERACTIVE AUDIOVISUAL DISTRIBUTION SYSTEM

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. Application Serial Number 08/711,583 filed November 15, 1997, which is a continuation of U.S. Application Serial Number 08/284,846 filed August 2, 1994, now issued as U.S. Patent No. 5,555,441.

BACKGROUND OF INVENTION

1. Technical Field

The present invention relates to an interactive communication system that allows a plurality of subscribers to access a central audiovisual library, more specifically, a system capable of handling each subscriber's tailored requests for program segments.

2. Background of Related Art

Systems which provide subscriber access to prerecorded program segments from a distributor center have been described. For example, in a system described in Patent No. 4,521,806 to Abraham, a plurality of subscribers are able independently to access segments of a central program library. The requested broadcast segments are digitized and time compressed at the central station. They are then delivered to the requesting subscriber only. The time compressed segments are recorded at the subscriber station by a two-speed recorder. When the transmission of the requested segment is complete, a broadcast signal attached to the end of the broadcast segment causes the two-speed recorder at the subscriber station to playback immediately the transmitted segment. In this system subscriber viewing time is a function of the program delivery time.

In a system described in Patent No. 4,751,684 to Clark et al., each system subscriber is able to request program segments from a distribution center. These segments are then delivered to all subscribers indiscriminately. Subscriber requests to the center are

placed in line in the chronological order in which they are received, and are broadcast in turn on one common channel.

U.S. Patent No. 4,963,995 to Lang discloses a video recorder/transmitter apparatus that enables a user to receive, compress, edit, and retransmit video program information in either compressed or decompressed format. The apparatus includes memory for mass data storage. The patent proposes the linkage of a plurality of the apparatus to a network transfer system, with one apparatus acting as a distribution center. The above-mentioned U.S. Patent Nos. 4,521,806; 4,751,684; and 4,963,995 are incorporated herein by reference.

Other recent audiovisual delivery systems include pay-per-view (PPV) and video-on-demand. Both systems offer real time or near instantaneous delivery of subscriber requested video programs in exchange for fees. Both systems emulate an on premise or home video store. But different from a video program rented from a video store, a drawback of these systems is the inability of the subscriber to manipulate the video program, such as rewind, pause, fast forward, etc., while it is being played or delivered. Further, the fees charged to the subscriber requesting the video program are based on the amount of time the subscriber accesses or is on the system. In contrast, a user who rents video programs from a video store may choose to access the program as many times and whenever he chooses without incurring further charges.

Therefore, there exists a need for an audiovisual delivery system that is efficient for the program

-2-

1 distributor while accommodating the individual needs of each
subscriber. More particularly, a system capable of handling
subscriber requests of several time allowance intervals
within which program segments will be delivered. The program
5 distributor accumulates like orders and has the option and
capability to fill each of these like orders simultaneously.
The subscriber is subsequently able to manipulate and view
segments or an entire delivered program.

10 ## SUMMARY OF THE INVENTION

To achieve these goals the system according to
the present invention provides for subscribers not only to
have unlimited access to a program library, but also to
select variable time allowance intervals for each program
15 requested. The subscriber is not choosing "yes" or "no" to
predetermined times of the day for delivery, as in PPV
systems. Instead, by choosing a variable time allowance
interval, (s)he is indicating the minimum and maximum amount
of time (s)he will wait for the deliver of a request, with
20 those minimums and maximums dependent upon, and beginning
with, the time that a request is placed.

The system according to the present invention
allows a plurality of subscribers to select any recorded
program of a central audiovisual library, without the
25 constraints of a central broadcast menu preselected by the
distributor. The system further allows a subscriber to
receive and store his selection(s), and to view them
subsequently at any time he chooses. Independent viewing by
each subscriber is made possible by linking a temporary

30

-3-

35

1 storage unit with a microprocessor and keypad at each
subscriber location. With microprocessor control of the
temporary storage unit, the system further allows for a
predetermined amount of time that a program request can be
5 viewed by a subscriber, that amount to be determined by the
subscriber or the system distributor.

An object of the system according to the
present invention is to allow for off-peak delivery of
requested programs. The present invention addresses the
10 issues of affordability, efficiency, and subscriber appeal.
In most audio-visual distribution systems the greatest
consumer demand occurs in the early evening hours. This peak
demand taxes the distribution network and may cause
distributors to limit consumer choices. The present
15 invention allows the distributor to shift much of the demand
away from the peak hours without limiting the consumer to a
pre-set or limited menu of programs.

In the present invention the distributor
provides the subscriber with several variable time allowance
20 intervals for delivery of requested programs. For example,
the distributor can offer "express delivery", that is, within
one hour; "one day delivery:, that is within a twenty-four
hour period; or "long term delivery", within seven (7) days.
Each time allowance interval is defined by the maximum amount
25 of time it will take for the order to be filled. Longer term
time frames can allow a minimum of time to elapse before
delivery. For example, the seven (7) day time frame can be
structured so that the program segments will be delivered
before the end of seven days, but not before a specified

30

-4-

35

1 time, for example, twenty-five (25) hours. In this way, the
subscriber can anticipate his or her future program
selections and place them at a much earlier date without
prematurely burdening his own storage capabilities. The
5 system of the invention also allows the subscriber to waive
the minimum time before delivery in those instances where his
own storage capacity would not be overburdened. If the
subscriber, for example, chooses a seven (7) day delivery
service, he can waive the twenty-five (25) hours delivery
10 minimum and receive delivery anytime within seven (7) days.
The subscriber will choose which of these time frames meets
his needs on any given occasion. Product prices will vary
accordingly. Pricing strategies will encourage distribution
during off-peak hours and thereby utilize the system hardware
15 more fully. Not all program segments need to be available
for each interval.

Another object of the present invention is to
allow identical orders to accumulate within a given time
period. The distributor has the option and the capability of
20 delivering simultaneously all or several requests for the
same program segment as long as there is some overlapping
time period for the associated time allowance intervals as
defined by the various requests. The feature of allowing
order accumulation provides maximum efficiency and
25 flexibility for the distributor. The distributor is able to
use the variability of the time intervals as a basis to
employ an optimization strategy. The advantages derived from
the optimization include a lower overall cost.

30

-5-

35

1   Still another object of the present invention
is to provide viewing time independent of transmission
(delivery) time. The system described herein enables the
subscriber to order and store one or more program segments.
5 At any time after transmission, the subscriber can view the
program segment entirely or in part. The number of viewing
times may be limited to a predetermined number, except in
those cases where the subscriber has purchased the program
segment through the system.

10

BRIEF DESCRIPTION OF THE DRAWINGS

          Other objects, features and advantages of the
present invention will become more readily apparent from the
following detailed description of the preferred embodiments
15 and the accompanying drawings:
          Figure 1 illustrates the audiovisual
distribution system according to the present invention;
          Figure 2 shows the major component of the
distribution center;
20   Figure 3 shows the major components of a
subscriber terminal;
          Figures 4 and 5 are a flow diagram of an order
processing module;
          Figure 6 and 7 are a flow diagram of a
25 feasibility scheduling module;
          Figure 8 is a flow diagram of a delete order
module;
          Figure 9 is a flow diagram of an optimal
scheduling module;

30

35

Figure 10 is a flow diagram of a transmit
module;

Figure 11 shows flow diagrams for a start-up
module and receive module;

Figure 12 shows a flow diagram of a request
module;

Figures 13 and 14 show a flow diagram of a
process order module;

Figure 15 is a flow diagram of a select view
module; and

Figure 16 is a flow diagram of a view module.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Briefly, the system according to the present
invention preferably utilizes a compressed digital video
technology to provide for transmission of full motion video
programs from a central distribution center to individual
subscribers which are connected over a communication network.

The system provides high speed communications,
preferably 1.544 Mbits/sec or higher, to carry video program
segments from a distribution center 100 to a plurality of
subscribers 110. The system also provides a low speed bi-
directional communication link which can be used for
controlling the video transmission. The system can further
use high speed dial-up transmission with calls to subscribers
originating from the telephone switching center. Permanently
connected links are also contemplated.

The high speed link 120, is preferably an
optical fiber link for transmission of program data from the

distribution center 100. The high speed link 120 may broadcast the same data to all subscribers, much the same as existing CATV systems. The high speed link may also use switching capabilities to facilitate services such as conferencing. It is apparent to one skilled in the art that other known communication techniques including wireless communication can be implemented to accomplish the features of the delivery system according to the present invention. The low speed link 130 is preferably a communication link via modems and dial-up telephone lines. It provides a duplex (two-way) channel for order requests and confirmation. A subscriber terminal 140 at each subscriber location is configured to receive those programs that have been confirmed through the order entry subsystem at the distribution center. The transmission could be encoded to prevent unauthorized reception. Unlike typical computer communication protocols, there is no need for the subscriber terminal to acknowledge whether a data packet has been received correctly. Occasional transmission errors are not critical in full motion video and would not be objectionable. The high speed and the low speed links described above can be combined into one link, such as the Bell System ADSL, for communicating the aforementioned information via a single bi-directional link.

For order entry processing on the other hand, the integrity of the transmitted data is extremely important, and full two-way handshaking is preferred. The amount of data in this case is moderate and relatively low speed. A modem speed of 2400 baud is usually sufficient.

-8-

DISTRIBUTION CENTER

The distribution center 100 performs the following major functions:

1.   Processes the incoming request for a video program from a customer.

        a)   receive incoming calls and establish the (low speed) communication link with a Subscriber Terminal.

        b)   provide authorization for the subscriber to receive and/or make a permanent copy of the program.

2.   Schedules the video program segments for transmission and determine whether an incoming order can be delivered at the requested variable time allowance interval.

3.   Controls the transmission of the video program segments.

4.   Maintains customer information and billing records.

5.   Maintains the library and catalog of video program segments.

The video programs are preferably available in compressed form and stored on an optical disk. Write Once-Read Many (WORM) or CD-Recordable technology can be used, with the disks stored in a jukebox arrangement. Manual intervention may be necessary to assure that the required program disks are loaded in the jukebox as needed.

Video compression techniques are known. Applicable compression techniques for the present invention include DVI (Digital Video Interactive from Intel Corp.) and

the Compressed Digital Video (CDV) technology from
Compression Labs, Inc. For an average compression ratio of
about 160:1 for VCR quality moving images, a frame of video
512x480 pixels x 3 colors (720 KBytes) can be reduced to 5
KBytes/frame. With a 30 frames/sec rate, the compressed
video requires 150 KB/sec. For a 90 minute (5400 sec) video,
total storage required is about 810 MB. The CDV technology
has a somewhat better image quality but requires 1.5
Mbits/sec (188 KBytes/sec) resulting in a little over 1 BGyte
for a 90 minute video. It is anticipated that with MPEG2,
high quality video could be provided at 3 to 5 Mbits/sec or
studio quality video at 7 to 10 Mbits/sec.

The system of the invention handles incoming
orders without interrupting the transmission of the video
programs. The distribution center includes multiple
processors for video transmission control. Preferably, each
processor transmits a separate video program. The
transmission scheme can be by ADSL, with a conference call
transmitting to multiple subscribers simultaneously.
Alternatively, the several programs can be time-division
multiplexed onto the optical fiber, providing better
utilization of the fiber capacity. In either case each
communication line may be serving subscribers in a particular
geographic area.

Order Processing

The Distribution Center includes an order
processing computer 200 which handles the communication with
the subscriber terminals over the low speed modem links 130,
processes incoming orders, and maintains the customer

1 information/billing data. Authorization to receive a
particular program or to make a permanent copy of a program
would be sent back to the subscriber terminals, along with
any encryption keys, if necessary, to decode the transmitted
5 program. The order processing computer 200 also determines a
schedule for transmitting the video programs and notifies the
transmission control processors 205 what programs to transmit
and when to transmit them. A display associated with the
order processing computer alerts an operator to load program
10 disks into the video library of the appropriate transmission
control processor.

The order processing computer 200 includes a
standard hard disk (not shown) for storage of customer
information and billing data as well as a catalog of video
15 programs. Depending on the number of subscribers and the
number of incoming orders anticipated, one or more additional
processors may be dedicated to handling telephone
communications and some of the order processing functions to
off-load the main order processing computer.

20 An interface bus, preferably IEEE-488
interface bus 215, links the transmission control processors
to the order processing computer for initiation of a video
program transmission and passing encryption keys. Several
transmission control processors can be connected on a single
25 IEEE-488, and more buses could be added as needed.

Video Transmission Control

The primary function of the transmission
control processors 205 is to retrieve video program data from
the video library 210, provide encryption or other receiver

30

-11-

35

1 authorization control, and transmit the data over the high
speed fiber link 120. The process of transmitting a program
is initiated on command from the scheduling function in the
order processing computer 200. Several transmission control
5 processors may be transmitting different video programs at
the same time using a time-division multiplexing scheme.

The video library 210 includes a set of WORM
optical disks or CD-Recordable disks that can be loaded into
a jukebox type disk reader. The memory 215, which may also
10 be a jukebox, can hold a number of disks and select the
appropriate one for access. The memory 215 holds over 1300
gigabytes of data and can be further expanded if necessary.
Other contemplated storage mediums include magnetic tape
systems that can automatically select and mount tape reels
15 from an extremely large archive library. A digital I/O board
220 is used to output the video data to the fiber optic
transmitter 230. This board provides for a transfer rate of
400 KBytes/sec with Direct Memory Access (DMA). At this data
rate, a 90 minute program can be transmitted in a little over
20 a half hour using DVI compression technology. The digital
I/O board may be a PDMA-32 which is commercially available
from Keithly-Metrabyte, or any substantially equivalent I/O
board having similar performance characteristics.

The capacity of the fiber optical link is in
25 the range of 270 Mbits/sec (33 MBytes/sec) to 1Gbit/sec (125
MBytes/sec). At the lower rate the link is capable of
handling about 80 different programs simultaneously. Using a
time division multiplexing scheme, packets from different
video programs would be intermixed on the fiber link under

30

-12-

35

control of multiplexing logic circuitry 225 interfacing the
several transmission control channels to fiber optic
transmitter 230. At the subscriber terminals, similar
demultiplexing logic circuitry would identify those packets
that a particular terminal was authorized to receive and
store them in a buffer memory, to be read in via the digital
I/O board.

The fiber optic transmitter 230 includes an
optical fiber transmitter/receiver module available from
Force, Inc., model #2666T-SCXX with data bandwidth of 50 Mb/s
to greater than 1 Gb/s at operating range 10 km to 20 km
(typical). The module connects to an Advanced Micro Devices
TAXI chip set (AM7968/AM7969) which in turn interfaces to the
multiplexor 225 described above. The multiplexor 225 can be
custom designed using the same technology as the TAXI chip
sets.

SUBSCRIBER TERMINAL

The major components of a subscriber terminal
110 are shown in Figure 3. A receiver 310 is connected to
the fiber optic link 120 for receiving the high speed optical
transmissions from the Distribution Center 100. The receiver
310 includes a photodiode for detecting the transmitted
optical data and converting the optical data to electrical
signals. A detector such as a Model #2666R-SCXX, available
from Force, Inc., is preferably used. The receiver 310 also
includes signal conditioning circuitry for reshaping the
detected signals. An AM 7969 TAXI chip, available from
Advanced Micro Devices, is preferably used.

-13-

1   A demultiplexer/decoder 320 demultiplexes the
received signals previously multiplexed by multiplexor 225 of
the Distribution Center 100 and digital I/O board 330
interfaces the demultiplexed data to the video and data
5 distribution circuitry, which includes a terminal processor
340, a video processor module 350 and memory 360. The
terminal processor 340 is preferably a personal computer (PC)
which includes associated display, modified keyboard
(keypad), hard disk memory, and/or WORM or CD-recordable
10 memory. The terminal processor 340 is also connected to
telephone link 130 through modem 370 for communicating with
the Distribution Center 100 including requesting and
receiving authorization for selected program segment orders.
        Video processor 350 decompresses the video
15 data received from the digital I/O 330 and provides Red-
Green-Blue (RGB) video outputs and Hifi/stereo audio outputs.
The video processor 350 may be an Action Media 750 available
from Intel. The compressed video program data may be stored
on one or more magnetic hard disks for temporary storage and
20 a WORM or CD-Recordable disk for a permanent copy. If more
than one hard disk is used, a previously received program
could be viewed at the same time that a second program is
being received. To store three 90 minute video programs in
temporary storage, approximately 2.2 GBytes of memory are
25 required.
        As an alternative to temporary storage of
video programs at the subscriber terminal, a pool of hard
disks located at the Distribution Center could provide real
time transmission. These disks would receive program
30

                        -14-

35

1 segments from the transmission control processors as
requested by subscribers.

Order entry may be selected through a menu
driven process using the PC keyboard and monitor. With this
5 approach the keypad would only need a set of number keys plus
an ENTER key. The subscriber terminal 110 dials up the
distribution center 100 to process orders and to receive the
authorization codes and/or encryption keys to receive the
program. The program would be stored on the magnetic disk,
10 and if authorization for permanent copy is received, it would
be copied to the WORM optical disk as convenient. Programs
could be copied from temporary to permanent storage only when
authorization is received from the order processing system.

DISTRIBUTION CENTER SOFTWARE

15 The software architecture for the Distribution
Center includes five primary processing modules and
preferably five databases. The processing modules are
loosely coupled and operate on an event-driven basis. They
perform the following general functions of: (1)   Order
20 processing - processes the incoming request from a customer;
(2)   Scheduling - schedules the video program segments for
transmission; (3)   Transmit - controls the transmission of
the video program segments; (4)   Customer
maintenance/billing - maintains customer information and
25 billing records; and (5)   Library maintenance - maintain the
library and catalog of video program segments.

The databases are organized as follows:

1.   Library - contains the currently
available video program segments in compressed format ready
30

35

1   for transmission. Each video program segment may be contained on a separate WORM or CD-ROM disk arranged in a jukebox type format.

2.   Catalog - list of current titles in the
5   Library database, including pointers to the corresponding library disk volume. For each entry, it contains the program length, the price schedule for the various classes of service, and recent statistics on customer demand (for use in optimizing the transmission schedule).

10   3.   Customer - contains customer information and billing records plus passwords and other information needed to authenticate customer identity on receipt of a dial-in request.

4.   Orders - current list of customer orders
15 to be delivered. Identifies the customer by a key into the Customer database and the video segment by a key into the Catalog database.

5.   Schedule - current schedule of video program segments to be transmitted. This database further
20 includes:

a)   Feasible schedule - used to determine whether a requested delivery is possible. It is organized by time slot and has each video segment delivered at the last
25   possible moment to satisfy requested variable time allowance intervals.

b)   Optimal schedule - an optimized schedule, organized by hardware delivery channel, showing the video segment currently being

30

-16-

35

transmitted (including start/end times,
etc.) and the next segment scheduled on
that channel.

Each entry includes receiver authorization
codes and keys into the Orders and Catalog databases.
A description of each module follows.

Order Processing

The Order Processing module provides the
interface by which the customer enters a request for a video
program segment.   A representative flowchart of the order
processing module is shown in Figures 4 and 5 as follows:

On receiving an incoming phone call over a
modem (405), the call is answered and a NewOrder data object
is created (405) for processing this call. Note that several
instances of these data objects may exist at the same time as
simultaneous incoming requests are processed. The following
functions are performed for each NewOrder data object.

a)   Validate the customer by retrieving the
customer ID information (410) and checking information in the
Customer database (415) and save the key into that database.
If the customer cannot be validated (420), send sign off
message and terminate call (430).

b)   If this customer has an outstanding order
(435, 445), prompt over the modem phone link whether an
existing order is to be changed or a new order is to be
entered (450). If an order is to be changed (455), prompt
for the changes interactively and process them (steps 460 to
490). For any changes in variable time allowance interval,
the Scheduling module must be called to update the Feasible

-17-

Schedule (470) and, if a higher variable time allowance interval is requested, to determine whether the delivery is feasible.

c)   Prompt the customer for a new order by interactively presenting the list of titles from the Catalog database, along with ordering instructions and pricing (510). If the customer enters an order (515), save the key into the Catalog database for that video program segment and proceed to the next step.   Otherwise, go to confirmation and sign off routine(s).

d)   Invoke the Scheduling module to verify whether the video program segment can be scheduled in the variable time allowance interval that the customer requested. The Feasible Schedule is also updated at this time (520).

e)   If the program segment cannot be scheduled for the requested variable time allowance interval, notify the customer of the highest variable time allowance interval that can be scheduled and ask whether that is acceptable (525, 530).   If not acceptable (535), invoke the Scheduling module to delete this order from the Feasible Schedule and go back to step 510 above.

f)   Confirmation and sign off routine (545) — send the order confirmation, if any, to the subscriber terminal.   This includes the receiver authorization code to allow receipt of the transmission when it occurs and codes to determine how long or how many times the video program segment may be viewed before it is automatically erased.   A confirmation message is displayed to the customer (550). Send the authorization codes (555).   Preferably, each

customer is assigned a unique identification number and at
the beginning of each program segment, the ID is transmitted
in a data block along with the authorization code and/or
decryption code. This technique provides the flexibility to
change the mix of customers to receive a particular
transmission up to the time the program is actually
transmitted.

g)   Send sign off message to subscriber
terminal and hang up the phone (560).

h)   Order processing complete.   Delete the
NewOrder data object and go to step 400 to wait for a new
incoming call.

Scheduling

The Scheduling module has two primary
functions: (1) Feasibility - to quickly determine whether
it is possible to satisfy a customer's request for a
particular video segment at a certain variable time allowance
interval so that a pending order can be accepted or rejected.
This function is invoked from the Order Processing module
whenever a new order or a change to an order is received; and
(2) Optimization - uses a rule based approach to select the
next program segment to transmit over a channel when the
channel becomes free. The technique optimizes the delivery
of video segments that have been ordered to efficiently
utilize the available hardware channels while meeting
variable time allowance interval requirements. This function
is invoked just before a hardware channel is to finish
transmission of a video segment so that the selection can be

-19-

made from the current list of orders. For example, orders
for the same program segment having overlapping time
allowance intervals can be accumulated and accessed at the
appropriate delivery time so that the delivery to the
5 requested subscribers can be substantially simultaneous or
broadcasted.

For continually processing new orders without
interrupting the optimal schedule, each function maintains a
separate schedule for its own use as described under Schedule
10 Database section.

The variable time allowance interval may
include a minimum delivery time which determines the earliest
time that the program segment is to be available for viewing.
This is accomplished through the authorization codes, which
15 tell the subscriber terminal when viewing is permitted. The
actual transmission may occur early; however, such early
transmission should only be allowed when a subscriber
indicates that he has sufficient memory to receive the
program. If desired, the customer could be made aware that
20 the program segment is available before the minimum waiting
period and that an order could be processed to authorize
immediate viewing.

When the Feasibility function is invoked, it
receives the following information from the Order Processing'
25 module:

- Keys into the Orders and Catalog databases
- Program length
- variable time allowance interval requested

30

35

If the system is split geographically with a separate link(s) for each area, the link that serves each customer must be identified in the Customer database, and the schedule must contain two parts: the schedules for the communication lines and the schedules for the transmission control channels. If the fiber optic link is not geographically split, all subscriber terminals may receive the same transmissions, and the number of control channels should equal the number of program segments that can be multiplexed on the fiber link at any one time. Alternatively, with high speed dial-up transmission capability, each transmission control unit can be connected directly to any number of subscriber terminals, and any number of control units may be used (limited only by the number of different program segments in the library). In either of these cases only the control channels need to be scheduled.

Figures 6 and 7 are program flow diagrams of the Feasibility Scheduling process, generally as follows:

Determine the latest time that delivery can be completed for the requested variable time allowance interval;

Search existing Feasible Schedule for the requested video segment (605);

If the video segment is found (610) and if the scheduled time satisfies the requested variable time allowance interval (645) (assuming proper link schedule on a geographically split system), then return a code to Order Processing that the order can be accepted (675). Otherwise

copy the current Feasible Schedule into a tentative working schedule (615);

If the video segment is found (610) but the scheduling time does not satisfy the requested variable time allowance interval (645), remove the program segment from the schedule (650, 655). For a geographically split system, remove the program segment from the tentative schedule for the appropriate geographic link;

Insert the program segment into the schedule at the latest possible time. Maintain the latest time order by inserting at the proper location and shifting other segments forward if necessary and if possible. When trying to insert the program segment into the schedule, check for conflict with other program segments for the same customer at the same time, and, if there is a conflict, insert at the latest possible time when there is no conflict (620);

If the insertion was successful (625), save the tentative schedule as the new Feasible Schedule (660) and return a code that the order can be accepted (680);

Otherwise if there is no lower variable time allowance interval (630), delete the tentative schedule (665) and return a code that the offer must be rejected (685);

If a lower variable time allowance interval exists, lower the variable time allowance interval, and try to insert the segment into the schedule (635);

If successful, save the tentative schedule as the new Feasible Schedule (640, 670) and return (690), indicating the highest variable time allowance interval than can be scheduled. Otherwise, go back to step 630.

For a geographically split fiber link system,
the insert program segment routine (steps 620, 635) is
expanded as shown in Figure 7, to first schedule (705, 710)
the link and then the channel (715 to 730) so that
coordination between different links can be effected.

Figure 8 is the flow process when the
Feasibility function is invoked by the OrderProcessing module
to delete an order from the Feasible Schedule. The process
include:

Search the Orders database for other orders of
this same video segment (805).

If no other order exists (810), then remove
the video segment from the Feasible Schedule (815, 820).

If the order exists, get the latest delivery
time for the new segment and move segment later in the
schedule if possible (825, 830).

Return to the calling program (835).

The Optimization function is invoked (via a
timer scheduled by the Transmit module) just before a
hardware channel completes delivery of its video segment.
Sufficient time is allowed so that the optimization can be
completed. The function may also be invoked if the Transmit
module finds that the schedule needs to be reoptimized before
initiating the transmission of a video segment. This
function selects only the next video segment to be
transmitted for each hardware channel. It is not practical
to try to optimize the complete schedule since new orders
would require it to be continually reoptimized.

-23-

Referring to Figure 9, the first step in the
processing is to calculate the slack time for each program
segment in the Feasible Schedule (905). The slack time is
the time remaining before a program segment must be started
to just meet its required delivery. It can be obtained
directly from the Feasible Schedule; however, if there were a
conflict in scheduling two or more program segments at the
same time for any customer, then the minimum slack time over
all of the conflicting programs is used as the slack time for
each of those programs. Next retrieve estimates of the rates
at which orders are expected to be placed for each program
segment at this day and time, including estimates for express
deliveries. These rate estimates can be computed off-line
based on recent statistics. The selection of the segment to
schedule for next transmission is based on the following
factors: (1) Slack time for each program segment to be
scheduled; (2) Estimated rate of arrival of orders for each
program segment to be scheduled; (3) Estimated rate of
arrival of orders for new program segments; (4) Estimated
rate of arrival of express orders for new program
segments:(5) How much free time is there in the Feasible
Schedule; (6) Current channel status, including when each
will become free; and (7) If any of the customers receiving a
transmission have other program segments on order and, if so,
when their current transmission is scheduled to be complete.
The selection of which segment is to be transmitted next on a
particular open channel is made by applying a set of rules to
compute a weight for each segment. This weight ranges from 0
to 1, and the segment with the highest weight is selected for

-24-

transmission (930). A weight is also computed for the channel to remain idle for a specified time period. The rules for computing the weights are listed below. Weights from the different rules are combined in the manner used to combine certainty factors as described in Rule Based Expert Systems: The MYCIN Experiments of the Stanford Heuristic Programming Project, B.G. Buchanan and E.H. Shortliffe, Eds., Addison-Wesley, Reading, MA, 1984, pp. 272-280. The descriptions in these pages are incorporated by reference herein.

1.   For each segment find how many channels will complete their current transmission within the slack time. Set the weight for that segment to the reciprocal of that number (910). If the number is one for any segment (915), select that segment immediately and return (920, 955). If there is more than one such segment, choose the one that is to be transmitted to the most customers.

2.   For each segment, add a small amount of weight inversely proportional to the estimated arrival rate of orders (925). For the idle channel weight use the rate of arrival of new program orders.

3.   Add a small amount of weight to each segment, proportional to the expected arrival rate of new orders up to a preset limit (925). This is to encourage the transmission of existing orders so that channels will be free later to handle new orders.

4.   Combine a small amount of negative weight proportional to estimated arrival rate of new express orders up to a preset limit. Add proportional weight to the idle

channel weight. The basis for the weight in this case is
moderate if there is a large amount of free time in the
Feasible Schedule; otherwise, it is small. The large or
small decision can be made by applying fuzzy logic. This
rule is to encourage leaving some channels free to handle
express orders. The program segment with the highest weight
is selected (930) and checked against the list of program
segments currently being transmitted (935). If there is a
conflict, the program segment with the next highest weight is
selected (940).

　　　If a channel is to remain idle by the
application of these rules (945), a timer is set to poll that
channel again in about 10 or 15 minutes (945, 950). The
amount of weight to be added in applying these rules (small,
moderate, etc.) is for a small weight to be preferably around
0.1 and a moderate weight to be around 0.3. The weights
could be updated as operating experience has gained. For
example, if the rate of arrival of express orders is less
than what has been experienced, the idle channel weight would
be reduced.

　　　For the geographically split system, the rules
should be applied to the Feasible Schedules for both the
channels and the links. An additional rule for coordinating
more than one link with a channel would be that once a
segment is selected for transmission on a particular link,
see if it is also needed on other links. If so, then wait
for those links to become available if the wait is not too
long and if it doesn't violate the slack time for other
segments on the new link.

-26-

Transmit

The Transmit module controls the actual transmission of the video program segment. It uses the Optimal Schedule to determine which segment to transmit over a particular hardware channel (steps 1000 to 1045). Keys obtained from the Optimal Schedule (1015) point into the Orders and Catalogue databases, which in turn contain keys into Customer and Library. When transmission of the program segment is complete, the corresponding entries in the Optimal and Feasible Schedules (1050) are deleted and all appropriate Customer records are updated to indicate that delivery has been made (1020, 1035). When transmission of a new video segment is initiated, a timer is set to start up the Optimization Scheduling function (1060) just before delivery is scheduled to complete.

Library Maintenance

This module (not shown) is used to add or remove available program segments to or from the Library and update the corresponding entry in the Catalog. It is initiated by operator selection from the main system menu.

Customer Maintenance/Billing

This module (not shown) is initiated by operator selection from the main system menu. There are two main functional areas that are involved:

- Update of all user information including that need to authenticate customer identity.

- Generate customer bills from the record of program segment deliveries in the Customer database.

1 Implementation of this module is readily apparent to an ordinarily skilled programmer.

SUBSCRIBER TERMINAL SOFTWARE

Through the PC keyboard and monitor at the

5 subscriber terminal, order entry and program viewing are controlled using a menu selection approach in which a set of options are displayed on the monitor and the customer enters his choice via the keypad. This technique is similar to that currently used for programming a VCR. The keypad need only

10 have a set of numeric keys (0-9) and an ENTER key. If desired a BACKSPACE key could be added to allow for correction of a miskey before ENTERing the selection.

When the customer wishes to make a request, for example to place or modify an order or to view a program

15 segment which he has already received, he presses the ENTER key. The system responds by displaying a menu on the video screen and waits for the customer to enter a response through the keypad by pressing the numeric keys that correspond to the desired menu selection and then pressing ENTER. If a

20 program segment was being viewed on the monitor when the ENTER key was pressed, that program pauses until the customer is finished with the menu selections. On return from the menus, the customer has the option to resume viewing the program, to stop viewing, or to select a different program.

25 The Subscriber Terminal subsystem is driven by two types of events which generate hardware interrupts: 1) a key being pressed on the keypad and 2) the communications hardware recognizing the start of a video program segment being transmitted over the communication line. Keypad events

30

-28-

35

are handled by the Request module or by a standard keyboard
processing routine, depending on the state of the system.
The communications event invokes the Receive module, which is
responsible for getting the incoming program segment off the
communication line and storing it to disk. The Receive
module can run in the background in a multi-tasking mode
while other processes such as order entry, program viewing,
or making a permanent copy are in progress.

The Subscriber Terminal software system
consists of seven modules, some of which are subroutines
called from the other modules.

Referring to Figure 11, the Start up module,
which is run when the system is first powered up (1100),
retrieves receive authorization codes (1105) and initializes
the communications hardware (1110) and then sets up the
interrupt processors for the keypad and the communications
hardware (steps 1115, 1120).

The receive module is invoked by an interrupt
from the communications hardware on the start of transmission
of a new program segment (1130). The module first checks
whether this Subscriber Terminal has been authorized (1135,
1140) (through the Process Order module) to receive the
program segment. If so, the module grabs the incoming blocks
of program data from the communication line and stores them
to disk (steps 1145, 1155 and 1160). The module continues to
run in the background (at high priority) in a multi-tasking
mode until all blocks of the program segment have been
received. Alternatively, the authorization code may be
transmitted to the subscriber terminal as described in the

1   Distribution Center Order Processing module. In that case,
    the Receive module examines the list of customers in the
    first block of a program segment to see if it is authorized
    to receive that program. If so, the authorization code that
5   is sent with that block is extracted to identify which of the
    subsequent blocks belong to that program segment.

            Referring to Figure 12, the request module,
    which handles all customer requests which are entered through
    the key pad (steps 1205, 1210, 1215). First, if a program
10 segment is being viewed, it notifies the View module to pause
    (1220, 1225). It then displays some basic menus to ask the
    customer whether he wants to process an order or to view or
    stop viewing a program segment (steps 1230, 1235, 1240,
    1245). Depending on the response, it calls the ProcessOrders
15 (1295) or the SelectView subroutines (1265), each of which
    presents more menu selections. A more complete description
    of this module is given below.

            The ProcessOrders routine is shown in Figures
    13 and 14. This subroutine is called by the Request module
20 or by the SelectView subroutine to interactively communicate
    with the distribution center. Subscriber orders or requests
    for extension of viewing time or number can be made through
    this routine. The subscriber dials up the Distribution
    Center and interfaces with the Order Processing module
25 (1305). The menus that are displayed by this module are
    preferably at the Distribution Center and passed as messages
    over the low speed communication link 130. Upon receipt and
    verification of the subscriber or customer ID information
    (1325, 1335), the distribution center sends a menu packet to
30

                              -30-

35

the subscriber (1340). These menus include lists of available programs, programs currently ordered but not yet delivered, pricing information, etc. The customer enters his response from the keypad and transmits that response back to the Distribution Center (1355). If an order is placed or an existing order is changed, the authorization codes are sent to the Subscriber Terminal. A more complete description of the module is given below.

The SelectView module is shown in Figure 15. This subroutine is called by the Request module to allow the customer to select for viewing any one of the programs segments that are available on the hard drive or the WORM drive at the subscriber terminal. If the selected program segment has expired (either date/time or number of plays), it asks the customer whether the order should be extended. If so, it calls the ProcessOrders subroutine so that authorization can be obtained from the Distribution Center. Otherwise, it asks if the program segment is to be deleted to free up disk space. Note that an expired program is not immediately deleted even though it cannot be viewed. This allows the customer to extend his authorization without the necessity of retransmitting the program segment. As an alternative implementation, the list of available programs could include those that have been received but not yet authorized for viewing because of the minimum wait time for the selected variable time allowance interval. The customer could be prompted to process an order to receive authorization for immediate viewing.

The View module is shown in Figure 16. This
module controls the actual viewing of a program segment. It
is initiated by the Request module after a selection has been
made using the SelectView subroutine. It may run at the same
5 time as the Receive module in a multi-tasking mode. A flag
or semaphore set by the Request module is used to tell the
View module when to pause in viewing a program. When a pause
flag is detected, the current program state is saved so that
viewing may be resumed later if desired. A parameter passed
10 to the view module identifies whether to resume a program, to
terminate a program, or to start a program from the
beginning.

The Copy module copies a program segment from
the hard disk to a removable storage medium such as a WORM
15 disk. It executes in the background in multi-tasking mode at
a very low priority.

Request module

This module is one of two modules that process
hardware interrupts from the keypad. When the system is
20 powered up, the start up module directs that any keypad
interrupts be processed by the Request module. All keys but
the ENTER key are ignored at this point, causing the module
returns immediately. When the ENTER key is pressed, however,
the module becomes ready to handle a customer request. It
25 first directs that keypad interrupts be processed by a
standard keyboard interrupt processor, which places key
presses in a queue where they may be accessed by standard
input functions. Next, it checks whether a program segment
is currently being viewed, and, if so, it sets the flag in

30

-32-

35

the View module to tell that module to pause. It then
displays a menu on the monitor and waits for a response to be
entered via the keypad (using standard input routines). The
menu options and subsequent actions are as follows:

        1.   Stop viewing (1240) (only if a program
segment was being viewed)

            invoke the View module to terminate the
current segment (1255). The program then
is no longer in the pause state.

        2.   Resume viewing (1250) (only if a program
segment is currently in the pause state)

        a)   direct the keyboard interrupt processing
to invoke this Request module (1280).

        b)   invoke the View module with "resume"
parameter (1282)

        c)   return (1283)

        3.   Process a new order (1285) (may be
selected at any time)

        a)   call the ProcessOrder subroutine with
"new order parameter" (1295)

        b)   go back to display a new menu on the
video screen (1230)

        4.   View a new program segment (1245) (only
if no program is currently in the pause state)

        a)   call the SelectView subroutine (1265)

        b)   direct the keyboard interrupt processing
to invoke this Request module (1280)

        c)   invoke the View module with "begin view"
parameter (1282)

d)   return (1283)

    5.   Permanent copy - customer has previously
purchased authorization to copy a program segment to a
removable storage medium such as a WORM disk (1201, 1202).

        a)   prompt customer to insert disk, wait for
              response (1203)

        b)   invoke the Copy module to copy the
              program segment to the removable medium
              in a multi-tasking mode at very low
              priority; continue execution of this
              module

        c)   go back to display a new menu on the
              video screen (1230)

    6.   Quit (only if no program is currently in
the pause state)

        a)   direct the keyboard interrupt processing
              to invoke this Request module (1280)

        b)   return (1283)

Notice that before returning from this module, the keypad
interrupt processor is set for this Request module.

Process orders subroutine

        This subroutine may be called from the Request
module or the SelectView subroutine. A parameter is passed
to indicate where it is called from. The first step is to
dial up the Distribution Center (1305) and establish
communication with the Order Processing module there. It
sends the customer identification information (1325),
including any passwords if desired, and tells whether to
process a new order (where this subroutine was called by the

                        -34-

Request module) or an extension to an existing order (where
this subroutine was called by SelectView). After receiving a
validation of the customer identification from the
Distribution Center, it waits for a message packet (1335,
1340). The message options are shown below with the
corresponding actions taken. All keypad entries are
processed using standard input routines where a number is
followed by ENTER.

1. Interactive messages (1345) - these are
the menus constructed by the Distribution Center to be
displayed on the video screen

     a)   display the message and wait for a
          response through the keypad (1350)

     b)   transmit the response back to the
          Distribution Center (1355)

     c)   go back to wait for another message
          packet from the Distribution Center
          (1340)

2. Authorization code for a particular
program segment (1375)

     a)   if this is for a new order, add the
          authorization to the list of program
          segments to be received (1390), transmit
          an acknowledgement to the Distribution
          Center (1360), and go back to wait for
          another message packet

     b)   if this is for an existing order that has
          been placed but not received yet, modify
          the authorization in the list of program

-35-

segments to be received (1395), transmit an acknowledgement to the Distribution Center, and go back to wait for another message packet

c) if this is an extension to the expiration status for a program segment already received, modify that expiration status (1395), transmit an acknowledgement to the Distribution Center, and go back to wait for another message packet

3. Check disk space (1400) - this code tells the Subscriber Terminal to verify whether there is sufficient disk space to store the requested program segment

a) If there is sufficient room (1405), transmit an acknowledgment to the Distribution Center, and go back to wait for another message packet (1410)

b) Otherwise, display a menu with the following options and wait for a response (1415):

i) cancel order (1420)

- transmit a cancel command to the Distribution Center (1425)

- go back to wait for another message packet

ii) delete file (1430)

- display a list of program segments with their size info & expiration status (1435)

-36-

1   -   wait for response
        -       if a program is selected (1440), delete
                it (1445) and go back to check if there
                is sufficient room; otherwise go back to
5   (b) and redisplay the menu.
            The system according to the invention is not
    limited to any specific means or methods of data
    communication between subscriber and distributor. For
    example, it is readily apparent to one ordinarily skilled in
10 the art that the distribution of programs can take place over
    CATV lines, fiber optic lines, or any other adaptable data
    link. Also without substantive changes, the system can be
    employed whether the method of distribution is a continuous
    loop, as in conventional CATV systems, or whether the method
15 uses dedicated or private lines, as in conventional telephone
    system. Regardless of the type of distribution link, the
    system provides interactive communication between subscriber
    and distributor, expanded memory for the subscriber, and a
    archive of time allowance intervals that provides maximum
20 flexibility for the subscriber and maximum efficiency for the
    distributor.

25

30

35